

6004 SERIES

Straight Line Action Clamps | Product Overview

Features:

- Similar in size to Model 604, with a solid body
- 50% more holding capacity than 604
- May be mounted through a hole or in a tapped hole.
- Locks over center in the extended and retracted position

Applications:

- Assembly
- Checking fixtures
- Welding fixtures
- Tensioning devices

Also Available:

See page MC-ACC-1 for accessories

Covered under one or more U.S./International Patents


6004
6004-MM



6004-R
6004-MMR
with
DESTACO®
Toggle Lock
Plus



Technical Information | Holding Capacities | Dimensions



Model	Max. Holding Capacity	Weight	EF:AF (pushing)	Plunger Travel	(M) Plunger Thread	Spindle (Recommended)	Mounting Nut (Supplied)
6004	[450 lbf] 2000 N	[0.81lb] 0,37kg	14.4:1	38 [1.50]	5/16-18	207203	606104
6004-MM		[0.89lb] 0,40kg			M8	207203-M	606104-M
6004-R	[450 lbf] 2000 N	[0.81lb] 0,37kg	14.4:1	38 [1.50]	5/16-18	207203	606104
6004-MMR		[0.89lb] 0,40kg			M8	207203-M	606104-M

HC = Holding Capacity, EF = Exerting Force, AF = Applied Force

